Better meetings with IAdea signboard

8/29/2016

Next UP 2016 Product Roadmap 15:30





NFC

NFC Option







Glass











Flush Mount Installation

Elegant Product Desian

Instant On-site Bookina



MEET ROOM

Authenticating access request

Enhances room management efficiency with touch-enabled authentication of IDs.

Brandable with LED lightbar

Thousands of colors to choose from to signal room status and showcase corporate identity.



Learn more about our software partners here



▲ 1-wire Installation

Easy installation with PoE (Power over Ethernet), which transmits power and information



Instant on-site booking Increases operation efficiency by eliminating time-consuming typing and submitting via website, but instead, allowing meetings to be booked directly from the panel in-person.



Flush mount + VESA mount + Glass mount

Unlike most typical signboards, XDS-1078 is flush mounted and much closer to the wall to deliver a much more visually pleasing and user intuitive industrial design of the system. IAdea provides step by step mounting guide, as easy as 1, 2, 3.







Flush mount

AC Adapter

installation

non-condensing

• Weight: 727g/1.6 lb

· Outer Carton Size:

Individual Package Size:

• Units per Outer Carton: 10

Output: 12V, 1.5A

Expansion Options

16GB/32GB micro SD/SDHC memory card

· Interchangeable connector system includes US

Dimensions for Product & Package

269.88mm(W)x 170.77mm (H)x 28.5 mm (D)

plugs (Option for EU, UK and AUS plugs)

Power-over-Ethernet (PoE) single-wire

• Input: 100-240V, 50-60 Hz, 0.5A Max.

UL/CB certified power supplies

Glass mount

Technical Specification

Open Standards Supported

- · HTML5, JavaScript, and CSS
- Android 4 4 API
- . W3C SMIL for cross-platform management
- W3C Widgets for HTML delivery .
- . POPAI Digital Signage Content Standards, including
- S1 (JPEG 480p baseline)
- S2 (JPEG 720p baseline)
- S4 (MPEG L2 audio)
- S5 (MP3 audio, 384Kbps)
- S6 (MPEG-1 SIF, 3Mbps CBR) .
- S7 (MPEG-1 480p, 10Mbps CBR)
- S8 (MPEG-1 720p, 15Mbps CBR) • S9 (MPEG-2 480p, 6Mbps CBR)
- S10 (MPEG-2 720p, 12Mbps CBR)
- . S11 (H.264/MPEG-4 AVC, 480p, 6Mbps CBR)
- S12 (H.264/MPEG-4 AVC, 720p, 10Mbps CBR) .
- E1 (PNG 24bpp+alpha, 480p)
- E2 (PNG 24bpp+alpha, 720p)
- E4 (VC-1/WMV9, MP@ML, 720p)
- E7 (MPEG-4 ASP, 480p, 10Mbps CBR)
- E8 (H.264/MPEG-4 AVC, 1080p, 20Mbps CBR

Advanced Signage Features

- · Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continued playback even when network is not available

HTML5 Support

- Widgets for calendar, clock, news, weather, Twitter, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

Display and Sound

10.1" LCD wide aspect ratio

- 10 points multi-touch
- 300 nits maximum brightness
- View Angle: 170 x170

Content Management

- SianApps Express Utility

Connectivity

- Wi-Fi:802.11 b/g/n

Local Storage

- 8 GB eMMC memory (approx. 360 minutes of typical 720p video @3 Mbps)
- Micro SD card slot (support up to 32GB storage)

Mounting Kit

- Built-in VESA compatible 75x75(mm) posts
- · Flush mount back cover and glass mount (optional)

Supplied Accessories

- Table stand
- . Adapter
- Power plug
- DC in & Micro SD stopper
- HW & SW QSG

Warranty

Certifications

CE/FCC

· 1-year limited parts & labor

IAdea Headquarter

3F, No. 21, Lane 168, Xingshan Road Taipei, Taiwan 114 Phone: +886-2-2791-1110 Fax: +886-2-2791-1170 Email: Sales@IAdea.com

IAdea America Corp.

20 Fairbanks, Suite 170 Irvine, CA 92618 Tel: +1-949-305-6489 Email: US-Sales@IAdea.com





1280x800 high resolution

- Built-in stereo speakers 1W x2
- Programmable LED bar x 2
- HDMI output to external display

- 3rd party solution (optional license)

- Multi-points touch
- Ethernet 10/100 BASE-T
- 3.5mm analog stereo audio out
- USB 20×2
- Micro USB for ADB
- Optional 3G/4G mobile module via USB
- External NFC module (optional)

Environmental • Operating temperature: 0 to 40°C

Size

Storage Humidity: 10 to 85% @ 40°C,

10.62" (W) x 6.72" (H) x1.12"(D)

13.2"(W) x 3.93"(H) x 8.93 (D)

336mm (W) x 100mm(H) x 227 mm (D)

695mm (W) x 260mm (H) x 530 mm(D)

27.36"(W) x 10.23"(H) x 20.86"(D)