

Meeting A Room A Meeting A 10 125 12019 3:30 AM Meeting A Mee

Glass Mount Solution for IAdea 10" All-In-One Display

IAdea 10" All-In-One Display can be professionally glass mounted to your office windows as your corporate digital signage by using our PGM-001 glass mount solution. It helps your workplace to communicate corporate event, meeting schedule, and directly increase brand recognition and corporate culture.

Industrial Heavy Duty

Our solution uses 3M VHB[™] Industrial Heavy Duty Mounting Tape. It holds XDS-1078 permanently to the glass for months.

Flush Mount, Yet Easy To Use

No screws, rivets, or welding; the signboard just mounted seamlessly against the glass window.





PGM-001 User Manual



XDS-1078 Product Page



	3M VHB™ Industrial Heavy Duty Mounting Tap	Cover Sheet
Color	Clear	Grey
Dimension	90 mm x 70 mm x 1 mm (3.52" x 2.75" x 0.04")	210 mm x 297 mm (8.3" x 11.7")
Installation Temperature Range	Ideal range: 21 °C to 38 °C (70 °F to 100 °F) Suggested minimum: 10 °C (50 °F)	N/A
Functional Temperature Range	-40 °C to 93 °C (-40 °F to 200 °F)	N/A
Maximum Load	2,000 g (4.4 lb) ** Total XDS-1078 weight: 925 g (2.04 lb) including Ethernet cable and power adaptor	N/A

Product Photos



3M VHB[™] Industrial Heavy Duty Mounting Tape 3M and VHB[™] are trademarks of 3M Company



Grey cover sheet

Packaging

	3M VHB™ Industrial Heavy Duty Mounting Tape	Cover Sheet
Option 1	x 2	x 2
Option 2	x 10	x 10

Disclaimer

IAdea has tested the solution thoroughly in many different conditions and has found satisfactory. However, PGM-001 Glass Mount Solution for IAdea 10" All-In-One Display is only recommended to be used on standard glass surfaces which have not been treated with decorative materials such as frosting spray or window film. The functionality and performance of the 3M VHB[™] tape and cover sheet can be affected by a variety of factors which are highly difficult to identify. It is the responsibility of the users to fully evaluate the product and determine whether the product is suitable for their intended purpose and method of application. The information delivered in this manual are based on tests and experiences presented by the 3M VHB[™] supplier. IAdea cannot make any guarantees on the accuracy and completeness of the technical information provided by the 3M VHB[™] supplier.



IAdea Headquarter

3F, No. 21, Lane 168, Xingshan Road Taipei, Taiwan 114 Phone: +886-2-2791-1110 Fax: +886-2-2791-1170 Email: Sales@IAdea.com

IAdea America Corp.

20 Fairbanks, Suite 170 Irvine, CA 92618 USA Tel: +1-949-305-6489 Email: US-Sales@IAdea.com



www.IAdea.com