



XDS-1588




PoE



Touch



Tempered Glass



Light Bar



NFC & RFID
Option



HID
Technology
Partner
HID
Optional



Elegant Product
Design



Instant On-site
Booking

Smart Workplace series: 15" widescreen all-in-one interactive display

The XDS-1588 is a 15" touch-enabled smart signboard with all the industry's best features XDS-2288 (sister model) has to offer, in addition to a built-in NFC module, as part of IAdea Smart Workplace series. Designed with industrial-grade robustness and performance, this is the best digital signage solution for every workplace and every corporation.



◀ Branding with Light Bars

Choose from thousands of programmable colors for your XDS-1588 LED light bars to provide the meeting room status. HR department would love to visually enhance the office with the use of corporate branding color to strengthen employee bonding.



Identification Made Easy ▶

Meetings get hectic in busy workplaces. Luckily XDS-1588-A comes with built-in NFC & RFID function for ID authentication and attendance tracking. The 15" meeting room signage is also compatible with various meeting room software platforms enabling seamless integration with any existing in-house enterprise room booking systems.



IAdea Ecosystem Partners
www.iaidea.com/ecosystem




▲ One Wire Does It All

The all-in-one smart design allows for XDS-1588 to be connected to power and network while enabling remote management for updates and control, all by using a single Ethernet cable. The word "single" has never sounded so exciting.



Product Photos



Technical Specification

Display <ul style="list-style-type: none"> 15.6" IPS LCD panel 10 points capacitive multi-touch 300 nits maximum brightness 1920 x 1080 (Full HD) panel resolution Viewing angle (H/V): 178/178 Programmable LED bar x 2 	HTML5 Support <ul style="list-style-type: none"> Widgets for calendar, clock, news, and web page integration HTML5 technologies including CSS and Javascript WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers 	Supplied Accessories <ul style="list-style-type: none"> Power adapter and plug Flush mount bracket Quick guide
Internal Player <ul style="list-style-type: none"> Processor: Cortex-A17 1.8 GHz Quad-Core System memory: 2.0 GB Flash memory: 8 GB eMMC built-in 	Advanced Signage Features <ul style="list-style-type: none"> Remote commissioning AlwaysOn, AppLock to prevent unauthorized access StrongCache for continuous playback even when network is not available Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker Auto-play starts playing scheduled contents automatically when power is re-established Automatic error recovery with built-in WDT Real-time clock with backup clock battery 	Power Requirement <ul style="list-style-type: none"> Input: 100 - 240 V, 50 - 60 Hz Output: 12 V, 2 A UL / CB certified power supplies Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs) Power-over-Ethernet (PoE+) single-wire installation
Video Format Supported <ul style="list-style-type: none"> H.264/AVC up to 1080p (1920 x 1080) H.265/AVC up to 1080p (1920 x 1080) MPEG-4 up to 1080p (1920 x 1080) MPEG-2 up to 1080p (1920 x 1080) MPEG-1 up to 1080p (1920 x 1080) VC-1 up to 1080p (1920 x 1080) 	Connectivity <ul style="list-style-type: none"> Front camera: 2MP Wi-Fi: 802.11 b/g/n Micro USB for ADB Ethernet RJ45 USB 2.0 x 2 Built-in 2 W stereo speakers x 2 3.5 mm analog stereo audio out Optional 3G / 4G mobile module via USB SD card slot, memory expendable to 16 GB / 32 GB / 64 GB (card replaces internal storage) 	Environmental <ul style="list-style-type: none"> Operating temperature: 0 to 40 °C Humidity: 10 to 85 % @ 40 °C non-condensing
Image Format Supported <ul style="list-style-type: none"> JPEG up to 1920 x 1080 PNG up to 1920 x 1080 	Mounting Options <ul style="list-style-type: none"> Built-in VESA MIS-D 100 mm x 100 mm mounting points 	Dimensions for Product & Package <ul style="list-style-type: none"> System dimension: 402 mm x 253 mm x 30 mm (15.82" x 9.96" x 1.19") System weight: 1320 g (2.917 lb) Individual package dimension: 493 mm x 303 mm x 70 mm (19.4" x 11.92" x 2.75") Individual package weight: 2000 g (4.42 lb) Units per outer carton: 5
Audio Format Supported <ul style="list-style-type: none"> MP3 up to 320 kbps 	Certifications <ul style="list-style-type: none"> CE / FCC / RoHS 	Warranty <ul style="list-style-type: none"> 1-year limited parts & labor* (varies based on region, contact sales for more details)
Content Management <ul style="list-style-type: none"> SignApps Express Utility 3rd party solution (optional license) 		
Open Standards Supported <ul style="list-style-type: none"> HTML5, JavaScript, and CSS W3C SMIL for cross-platform management W3C widgets for HTML delivery Android 7.1 API 		

Available SKU

XDS-1588	IAdea standard.
XDS-1588-A	IAdea standard with NFC & RFID embedded.
XDS-1588-H	IAdea standard with HID module embedded.



IAdea Headquarter
 3F, No. 21, Lane 168, Xingshan Road
 Taipei, Taiwan 114
 Phone: +886-2-2791-1110
 Fax: +886-2-2791-1170
 Email: Sales@IAdea.com

IAdea America Corp.
 20 Fairbanks, Suite 170
 Irvine, CA 92618
 USA
 Tel: +1-949-305-6489
 Email: US-Sales@IAdea.com



www.IAdea.com