



XDS-1078-A9

Advanced 10.1" Interactive Room Panel

Industry's First Android 9.0 Meeting Room Panel — Highly Responsive & Secure



Android 9
By Google

Latest OS from Google. Continuous security updates for reliability




PoE+ / PoE

Minimalist installation keeps workplaces simple & modern



2.8 cm Slim Design

Built-in zero-gap flush for secure, versatile mounting




High Visibility Status Light

Elegant light bars with soft illumination that is easy on the eyes



Orientation Aware

Easy to integrate into workplace design in portrait and landscape



High Performance Processor

Powers smooth, responsive, and vibrant user experience



10-Point Multi-Touch

Quick check-in/out or book room at-the-door. Zoom and scroll for easy browsing



Remote Device Management

Easily manage, monitor & troubleshoot all in-service room panels

Mounting Options

Zero-gap flush
VESA mount



* Included in package

Table stand
PVK-102



Glass mount
PGM-001



Window mount
PWM-041



Tilt wall mount
PTM-101



Technical Specifications

Display

- 10.1" LCD panel
- 10 points capacitive multi-touch
- 300 nits maximum brightness
- 1280 x 800 panel resolution
- Viewing angle (H / V): 170 / 170
- 6 primary colors LED bar x 2

Video Format Supported

- H.264/AVC up to 1080p (1920 x 1080)
- H.265/HEVC up to 1080p (1920 x 1080)
- MPEG-4 up to 1080p (1920 x 1080)
- MPEG-2 up to 1080p (1920 x 1080)
- MPEG-1 up to 1080p (1920 x 1080)
- VC-1 up to 1080p (1920 x 1080)

Image Format Supported

- JPEG up to 1920 x 1080
- PNG up to 1920 x 1080

Audio Format Supported

- MP3 up to 320 kbps

Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

Open Standards Supported

- HTML5, Javascript and CSS
- Android 9.0 API
- W3C SMIL for cross-platform management
- W3C HTML5 widgets
- Support multimedia content playback such as video and image

HTML5 Support

- Widgets for calendar, clock, news, and web page integration
- HTML5 technologies including CSS and Javascript
- Chromium-based browser engine, same as Google Chrome™

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continuous playback even when network is not available
- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Auto-play starts playing scheduled contents automatically when power is re-established
- Automatic error recovery with built-in WDT
- Real-time clock with backup clock battery

Connectivity

- Wi-Fi: 802.11 b/g/n
- Micro USB for ADB
- Ethernet RJ45: 10/100 BASE-T
- USB 2.0 x 2
- Built-in 1 W stereo speakers x 2
- 3.5 mm analog stereo audio out
- Optional 3G / 4G mobile module via USB
- Micro SD card slot, memory expendable to 16 GB / 32 GB / 64 GB (card replaces internal storage)

Mounting Options

- Built-in VESA compatible 75 mm x 75 mm posts
- Flush mount back cover

Supplied Accessories

- DC in & micro SD stopper
- HW & SW QSG

Optional Accessories

- PGM-001 Glass Mount Solution
- PTM-101 Tilt Wall Mount
- PVK-102 Pivot Table Stand
- PWM-011 & PWM-041
- Premium Window Mount
- Table stand
- Adapter
- Power plug

Power Requirement

- Input: 100 - 240 V, 50 - 60 Hz
- Output: 12 V, 1.5 A
- UL / CB certified power supplies
- Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs)
- IEEE 802.3at Power over Ethernet (PoE+) / Eco mode on IEEE 802.3af Power over Ethernet (PoE)

Environmental

- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 40 °C non-condensing

Dimensions for Product & Package

- Display size: 269.88 mm x 170.77 mm x 28.5 mm (10.62" x 6.72" x 1.12")
- Display weight: 727 g (1.6 lbs)
- Individual package size: 336 mm x 100 mm x 227 mm (27.36" x 10.23" x 20.86")
- Outer carton size: 523(W)x356(D)x259(H)mm
- Units per outer carton: 5

Certifications

- CE / FCC / RoHS

Warranty

- 1-year limited parts & labor* (varies based on region, contact sales for more details)



America

20 Fairbanks,
Ste, 170 Irvine, CA 92618
California, U.S.A
Tel: +1-949-305-6489
Email: US-Sales@IAdea.com

Taiwan

114, 3F, No. 21
Ln. 168, Xingshan Rd.
Neihu Dist., Taipei, Taiwan
Tel: +886-2-2791-1110
Fax: +886-2-2791-1170
Email: Sales@IAdea.com

